

Ashbery Wall Mount Light

landscapeforms®

Product Data Sheet



Ashbery is a trio of lights that brings together advanced LED technology and optics with an homage to traditional-style lights that have a special place in the American lexicon. The wall mounted light is designed to provide soft lighting adjacent to buildings to extend the safe use of outdoor areas. Cast aluminum parts in a full color palette are finished with Landscape Forms proprietary Pangard II® HAPS, VOC, lead-free polyester powdercoat.

General Description

- Smaller scale fixture designed for wall mounted or pole applications
- Aluminum wall mounting bracket and arm included
- Optional ANSI136.41 7-pin twist lock receptacle
- International Dark-Sky approved
- UL Listed, suitable for wet locations

Electrical

Surge protected 100V-277V 50/60 Hz, Class 2 integrated dimmable driver. LED cartridge with weatherproof quick disconnect provides ease of installation and serviceability. Ashbery ships prewired.

Ashbery Wall Mount Light

Type 3 Distribution

CCT: 2700K, 3000K, 3500K, 4000K

Drive Current: 700mA

Optic: Khatod Collimators

Lens: Diffused Acrylite®

Power Supply: 100V-277V

LED Driver: 20W

Dimmable: 0-10V

BUG Rating: B0-U2-G1

IP Rating: IP66 for LED Cartridge

Weight: 28 lbs

Warranty

LED lighting products are warranted for six years.

Certification

UL Listed for Wet Location, CE, International Dark Sky Approved, Buy America Compliant, RoHS Compliant



[Click here](#) for patent information related to this product.



Ashbery Wall Mount Light

LED lighting facts®		
A Program of the U.S. DOE		
Light Output (Lumens)	1012	
Watts	19.25	
Lumens per Watt (Efficacy)	52.59	
Color Accuracy Color Rendering Index (CRI)	83	
Light Color Correlated Color Temperature (CCT)	3000 (Bright White)	
LED Lumen Maintenance Projection at 36,000 Hours at 25°C Ambient*		91.13%
Warranty**	Yes	

All results, except LED Lumen Maintenance, are according to IESNA LM-79-2008. Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

* Based on TM-21 projections for the light source.
** See www.lightingfacts.com/products for details.

Registration Number: 1Y17-EXL5RB (6/9/2016)
Model Number: Ashbery Wall Mount
Type: Luminaire - Area/Roadway



Ashbery Wall Mount Light



Product Data Sheet



Finish

Pangard II®, offered exclusively by Landscape Forms, is a 19 step program of cleaning, priming, and powdercoating that resists rusting, chipping, peeling and fading to produce the finest metal finish available for site furniture and outdoor lighting. In addition, Pangard II® contains no heavy metals and is free of Hazardous Air Pollutants.

To Order

Specify: Product, Drive Current, Color Temperature, Distribution, Lens, Center Element, optional Twist Lock Receptacle, and Powdercoat Color.

Product	Drive Current	Color Temperature	Distribution	Lens	Center Element	Twist Lock	Powdercoat
AP103 (Wall Mount)	SO (Standard Output)	27K (2700K)	T3 (Type III)	FRS (Frosted)	20K (2000K)	NTW (No Twist Lock) TW1 (Twist Lock)	See powdercoat color options on the Material / Colors Sheet.
		30K (3000K)					
		35K (3500K)					
		40K (4000K)					

Example: AP103 – SO – 27K – T3 – FRS – 20K – TW1 – Powdercoat

Visit landscapeforms.com for more information. Specifications are subject to change without notice. Landscape Forms supports the Landscape Architecture Foundation at the Second Century level.

©2022 Landscape Forms, Inc. Printed in U.S.A.

landscapeforms.com | specify@landscapeforms.com

